

Tape Twist – lock Fittings

Tavlit offers a range of fittings for various sizes especially suited to the USA market.

Features:

- Excellent resistance to mechanical pull:
Prevents accidental disconnection by people or machinery.
- U.V. protected for extended life in harsh conditions.
- Designed to resist high pressure and wide temperature range.
- High chemical resistance.
- Wide grips for easy assembly
- Streamlined design to allow automatic coiling.
- Easy grip on
- Made with reliability, long life and durability in mind.

Technical Specifications

- Maximum operating pressure 60 psi (4 bar).
- Material: Polypropylene
- Threads: N.P.T, F.H.T.

Tape Twist - lock coupling

| Cat. Number | Nominal size | Wall thickness mil (mm) | ID mm (Inch) |
|-------------|---------------|----------------------------|-----------------|
| CTT | 16 mm x 16 mm | 4 - 45 (0.10 – 1.1) | 16 (0.63) |
| CTT22 | 22 mm x 22 mm | 6 - 25 (0.15 – 0.63) | 22 (0.875) |
| CTT25 | 25 mm x 25 mm | 6 - 25 (0.15 – 0.63) | 25 (0.99) |



Tape Twist - lock male thread

| Cat. Number | Nominal size | Wall thickness mil (mm) | ID mm (Inch) |
|-------------|-------------------|----------------------------|-----------------|
| MHTA12TA | 1/2" Male x 16 mm | 4 - 45 (0.10 – 1.1) | 16 (0.63) |
| MHTA34TA | 3/4" Male x 16 mm | 4 - 45 (0.10 – 1.1) | 16 (0.63) |
| MHTA34TA22 | 3/4" Male x 22 mm | 6 - 25 (0.15 – 0.63) | 22 (0.875) |
| MHTA34TA25 | 3/4" Male x 25 mm | 6 - 25 (0.15 – 0.63) | 25 (0.99) |



Tape Twist - lock swivel female thread



| Cat. Number | Nominal size | Wall thickness mil (mm) | ID mm(Inch) |
|-------------|-----------------------------------|----------------------------|----------------|
| SA34TAFHT | 3/4" Female thread swivel x 16 mm | 4 - 45 (0.10 – 1.1) | 16 (0.634) |
| SA34TA22FHT | 3/4" Female thread swivel x 22 mm | 6 - 25 (0.15 – 0.63) | 22 (0.875) |
| SA34TA25FHT | 3/4" Female thread swivel x 25 mm | 6 - 25 (0.15 – 0.63) | 25 (0.99) |

Tape Twist - lock barb connector

| Cat. Number | Nominal size | Wall thickness mil (mm) | ID mm(Inch) |
|-------------|--------------------|----------------------------|----------------|
| TA1617 | 16,17 mm x16,17 mm | 4 - 45 (0.10 – 1.1) | 16 (0.63) |
| TA2220 | 22 mm x 20 mm | 6 - 25 (0.15 – 0.63) | 22 (0.875) |
| TA2525 | 25 mm x 25 mm | 6 - 25 (0.15 – 0.63) | 25 (0.99) |



Drip tape End line

| Cat. Number | Nominal size | Wall thickness mil (mm) | ID mm(Inch) |
|-------------|--------------|----------------------------|----------------|
| ELPTA | 16,17 mm | 4 - 45 (0.10 – 1.1) | 16 (0.63) |



Lay flat Starter

| Cat. Number | Nominal size | Wall thickness mil (mm) | ID mm(Inch) |
|-------------|--------------|----------------------------|----------------|
| LFTA | 16,17 mm | 4 - 45 (0.10 – 1.1) | 16 (0.63) |
| LFTA22 | 22 mm | 6 - 25 (0.15 – 0.63) | 22 (0.875) |



Stick Starter

| Cat. Number | Nominal size | Wall thickness mil (mm) | ID Mm (Inch) |
|-------------|--------------------|----------------------------|-----------------|
| STTA | 16,17 mm | 4 - 45 (0.10 – 1.1) | 16 (0.63) |
| STTAGR | 16,17 mm Inc. G-ST | 4 - 45 (0.10 – 1.1) | 16 (0.63) |
| STTA22 | 22 mm | 6 - 25 (0.15 – 0.63) | 22 (0.875) |
| STTA22GR | 22 mm Inc. G-ST | 6 - 25 (0.15 – 0.63) | 25 (0.99) |



P.V.C Starter

| Cat. Number | Nominal size | Wall thickness mil (mm) | ID mm(Inch) |
|-------------|---------------------|----------------------------|----------------|
| GSTA | 16,17 mm ,Inc. G-16 | 4 - 45 (0.10 – 1.12) | 16 (0.634) |

