

Hose – lock Fittings

Tavlit offers a range of heavy - wall drip fittings of various sizes.

Features:

- Excellent resistance to mechanical pull:
Prevents accidental disconnection by people or machinery.
- U.V. protected for extended life in harsh conditions.
- Designed to resist high pressure.
- High chemical resistance.
- Streamlined design to allow automatic coiling.
- Made with reliability, long life and durability in mind.

Technical Specifications

- Maximum operating pressure 120 psi (8 bar).
- Material: Polypropylene
- Threads: N.P.T, FHT.

Hose - lock coupling fittings

Cat. Number	Nominal size	Wall thickness mil (mm)	ID Inch (mm)
CTL16	16/17x16/17 mm	35-55 (0.89-1.40)	0.51-0.58 (12.9-14.7)
CTL18	18 x 18 mm	25-50 (0.64-1.27)	0.59-0.63 (15.0-16.0)
CTL20	20 x 20 mm	40-55 (1.0-1.4)	0.68-0.74 (17.4-18.9)
CTL23	3/4" X 3/4"	45-65 (1.14-1.65)	0.79-0.84 (20.0-21.5)
CTL25	1" x 1"	65-75 (1.6-1.91)	1.02-1.08 (26.0-27.6)



Hose - lock male thread fittings

Cat. Number	Nominal size
MPTA12TL18	1/2" Male thread x 18 mm
MPTA34TL18	3/4" Male thread x 18 mm



Hose - lock female thread swivel fittings

Cat. Number	Nominal size
SA34TL16FHT	3/4" Female thread swivel x 16/17 mm
SA34TL18FHT	3/4" Female thread swivel x 18 mm
SA34TL20FHT	3/4" Female thread swivel x 20 mm
SA34TL23FHT	3/4" Female thread swivel x 3/4" hose
SA34TL25FHT	3/4" Female thread swivel x 1" hose



Hose - lock swivel Tee fittings

Cat. Number	Nominal size
TSTL1634FHT	16/17 mm x 3/4" Female swivel x 16/17 mm
TSTL1834FHT	18 mm x 3/4" Female swivel x 18 mm
TSTL2034FHT	20 mm x 3/4" Female swivel x 20 mm
TSTL2334FHT	3/4" hose x 3/4" Female swivel x 3/4" hose
TSTL2534FHT	1" hose x 3/4" Female swivel x 1" hose

